




For Sleeving of Gas Pipes



GAS SLEEVING

GAS SLEEVING PIPE

Gas Sleeving pipe is a yellow pigmented pipe manufactured from a rigid PVC compound.

These yellow color coded pipes are designed exclusively to sleeve over gas pipes and help in eliminating damage to gas lines during construction and excavation.

Belled End Solvent Weld PVC Pipe
Schedule 40

- Cell Class 12454-B according to ASTM-D 1784 Type 1 Grade 1
- ASTM-D 2672 for solvent weld bell end pipe
- Available in belled ends
- Standard 20' Lengths
- Schedule 40 Diameters 1" to 6"

Schedule 40 - Belled End

Diameter Size	OD Nominal	ID Nominal	Min Wall Thickness	Max Wall Thickness	Working Pressure	Wt Per 100 ft	Ft Per Lift	Wt Per Lift
1"	1.315	1.029	0.133	0.153	450	32.5	5506	1788
1 1/4"	1.66	1.36	0.14	0.16	370	43.4	4400	1910
1 1/2"	1.9	1.59	0.145	0.165	330	51.8	3360	1740
2"	2.375	2.047	0.154	0.174	280	69.6	2100	1462
4"	4.5	4.026	0.237	0.265	220	203.4	1140	1953
6"	6.625	6.065	0.28	0.314	160	358.5	520	1884

GAS SLEEVING WARRANTY

GAS SLEEVING PIPE is warranted to be free of manufacturing defects in material and workmanship and to meet and perform to the specifications and standards imprinted on the product for a period of 5 years from date of purchase. If GAS SLEEVING PIPE proves defective due to manufacturing process in material or workmanship during the warranty period, U.S. POLYMERS, INC. will provide new replacement units of the same type and size at not cost. No remedy will be granted under this warranty if GAS SLEEVING PIPE is not used and/or installed in accordance with ASTM-D2855 and accepted industry standards with respect to use of recommended primer, solvent cement and proper joining methods, and install in accordance with all Federal, State and Local codes or laws governing the installation of such product. This warranty does not extend to claims arising from the use of the product as conduit for the transport or storage of compressed air and other compressed gases, or other uses not recommended by PVC industry or misuse or improper handling and/or installation of the product, nor does it extend to any losses except the replacement of the defective units. In all events this warranty extends to material only, and U.S. POLYMERS, INC. shall not be liable for any installation labor of defective or replacement material.

Proof of purchase with the date thereof must be presented to the satisfaction of U.S. POLYMERS, INC. with any claim made pursuant to this warranty. This warranty is in lieu of all other implied and expressed warranties, which are merged into it and expire at the end of this warranty period. All claims must be processed through the claimant's seller, and no replacement will be allowed by U.S. POLYMERS, INC. unless the reported defect has been inspected and approved for replacement by wither U.S. POLYMERS, INC., its authorized agent, or its representative.

For Pricing Contact USP Customer Service at 1-800-483-1361



GAS SLEEVING